Printing date 02/08/2016 Revised On 02/08/2016

1 Identification of the substance and manufacturer

DiamondFinish Clear Aerosol Trade name:

Product code: 8114

PC9a Paints and coatings. **Product category**

Advanced Protective Technologies LLC Manufacturer/Supplier:

1101 Cumberland Xing #180

Valparaiso, IN 46383 Phone: 8219-263-0073 kbs-coatings.com

Emergency telephone number: Chemtrec 800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Eye Irrit. 2A H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Skin Sens. 1

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements

GHS02 GHS04 GHS07 GHS08 Danger

Signal word Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe dust/fume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.
Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN: Wash with plenty of water.
Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
115-10-6	dimethyl ether	39.99%	
78-93-3	methyl ethyl ketone	15.64%	
108-65-6	PM acetate	14.57%	
108-94-1	cyclohexanone	8.28%	
108-88-3	Toluene	7.82%	
80-62-6	methyl methacrylate	0.12%	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	0.12%	

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a

doctor.

After swallowing: Rinse out mouth and then drink plenty of water.

(Contd. on page 2)

Printing date 02/08/2016 Revised On 02/08/2016

Trade name: 1K CLEAR

Rinse mouth with water. Do not induce vomiting.

(Contd. of page 1)

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective

equipment and emergency

procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEEL (USA) Long-term value: 1000 ppm

78-93-3 methyl ethyl ketone

Long-term value: 590 mg/m3, 200 ppm PEL (USA) Short-term value: 885 mg/m³, 300 ppm REL (USA)

Long-term value: 590 mg/m³, 200 ppm

TLV (USA)

Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm

BEI

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

108-94-1 cyclohexanone

PEL (USA) Long-term value: 200 mg/m3, 50 ppm REL (USA) Long-term value: 100 mg/m³, 25 ppm

TLV (USA) Long-term value: 50 mg/m³, 20 ppm

108-88-3 Toluene

TLV (USA)

Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm PEL (USA)

10-min peak per 8-hr shift

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm REL (USA)

Long-term value: 75 mg/m³, 20 ppm

Ingredients with biological limit values:

78-93-3 methyl ethyl ketone

BEI (USA) 2 mg/L Medium: urine

Time: end of shift Parameter: MEK

108-94-1 cyclohexanone

BEI (USA) 80 mg/L

Time: end of shift at end of workweek

Parameter: 1,2-Cyclohexanediol with hydrolysis (nonspecific, semi-quantitative)

8 mg/L

Medium: urine

Time: end of shift

Parameter: Cyclohexanol with hydrolysis (nonspecific, semi-quantitative)

(Contd. on page 3)

(Contd. of page 2)

Printing date 02/08/2016 Revised On 02/08/2016

Trade name: 1K CLEAR

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Melting point/Melting range Not determined. Undetermined. **Boiling point:** -24 °C (-11 °F) Flash point: -42 °C (-44 °F) Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % **Upper Explosion Limit:** 18.6 Vol % Not determined. Vapor pressure:

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. VOC content: 696.2 g/l / 5.81 lb/gl

VOC content (less exempt solvents): 87.3 % Solids content: 12.4 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: No decomposition if used according to specifications.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

	•			
LD/LC50 values that are relevant for classification:				
115-10-6 dimethyl ether				
Inhalative LC50/4 h 308 mg/l (rat)				
78-93-3 methyl ethyl ketone				
Oral		3300 mg/kg (rat)		
Dermal	LD50	5000 mg/kg (rbt)		
108-65-6 PM acetate				
Oral	LD50	8500 mg/kg (rat)		
Inhalative	LC50/4 h	35.7 mg/l (rat)		

(Contd. on page 4)

Printing date 02/08/2016 Revised On 02/08/2016

Trade name: 1K CLEAR

(Contd. of page 3) 108-94-1 cyclohexanone

LD50 Oral 1900 mg/kg (rat) 948 mg/kg (rbt) Dermal LD50 Inhalative LC50/4 h 8000 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

No sensitizing effects known. Sensitization:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-94-1 cyclohexanone 3 108-88-3 Toluene 3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A

DOT Consumer Commodity ORM-D

Aerosols, flammable 1950 Aerosols

Transport hazard class(es):

Class Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group: UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

SARA Section 313 (Specific toxic chemical listings):

78-93-3 methyl ethyl ketone

108-88-3 Toluene

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause developmental

toxicity:

CANADIAN ENVIRONMENTAL PROTECTION ACT:

108-88-3 Toluene

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. WHMIS Symbols for Canada:

- Compressed gas

Very toxic material causing other toxic effects

EPA: 78-93-3 methyl ethyl ketone 108-88-3 Toluene Ш

Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

16 Other information

Contact: Regulatory Affairs 02/08/2016 / -Date of preparation / last revision